

Zimbra

adriano.soares@tjam.jus.br

RES: PG EL n 046-2013 - informação Importante

De : Janice Nunes Centeno
<janice.centeno@intelbras.com.br>

Qua, 27 de Nov de 2013 10:12

 2 anexos

Assunto : RES: PG EL n 046-2013 - informação
Importante

Para : cpl@tjam.jus.br

Senhor pregoeiro,

Conforme documentação enviada pelo próprio fornecedor, o item XML Browser não é atendido pelo modelo T20P. Este item está destacado em amarelo no documento em anexo(enviado pelo próprio fornecedor) no item advanced features.

Janice Centeno
Analista de Licitações - ICORP
48 2108-3153
janice.centeno@intelbras.com.br



Matriz SJ:\nRod. BR 101, Km 210, Área Industrial\nSão José/SC - CEP: 88.104-800

www.intelbras.com.br

De: Janice Nunes Centeno
Enviada em: quarta-feira, 27 de novembro de 2013 11:44
Para: 'cpl@tjam.jus.br'
Assunto: PG EL n 046-2013 - informação Importante
Prioridade: Alta

Ao

TJ-AM

Informação:

Sr. Pregoeiro o primeiro colocado nesse pregão ofertou o aparelho T20P que não atende as especificações, pois esse aparelho não possui suporte XML Browser e programação da agenda telefônica via arquivo XML.

Att.,

Janice Centeno
Analista de Licitações - ICORP
48 2108-3153
janice.centeno@intelbras.com.br



Matriz SJ:\br/>Rod. BR 101, Km 210, Área Industrial
São José/SC - CEP: 88.104-800
www.intelbras.com.br



image001.jpg
1 KB



Yealink SIP-T2XP Specification(V71).pdf
214 KB

PG EL n 046-2013 - informação Importante

De : Janice Nunes Centeno
<janice.centeno@intelbras.com.br>

Qua, 27 de Nov de 2013 09:43

1 anexo

Assunto : PG EL n 046-2013 - informação Importante

Para : cpl@tjam.jus.br

Ao

TJ-AM

Informação:

Sr. Pregoeiro o primeiro colocado nesse pregão ofertou o aparelho T20P que não atende as especificações, pois esse aparelho não possui suporte XML Browser e programação da agenda telefônica via arquivo XML.

Att.,

Janice Centeno
Analista de Licitações - ICORP
48 2108-3153
janice.centeno@intelbras.com.br



Matriz SJ:\br/>Rod. BR 101, Km 210, Área Industrial
São José/SC - CEP: 88.104-800
www.intelbras.com.br



image001.jpg

1 KB

Specification of Yealink Enterprise HD IP Phones V71

Features	Model	SIP-T28P	SIP-T26P	SIP-T22P	SIP-T20P
General					
Picture		 Executive	 Advanced	 Professional	 Entry Level
Chipset		TI TITAN	TI TITAN	TI TITAN	TI TITAN
Flash memory		8MB	8MB	8MB	8MB
SDRAM memory		32MB	32MB	32MB	32MB
Dimensions (W*D*H*T ;handset on cradle,stand attached)		273mm x 200mm x 158mmx58.5mm	273mm x 200mm x 158mmx58.5mm	209mm x 188mm x 150mm x 41mm	209mm x 188mm x 150mm x 41mm
Weight (handset on cradle, stand attached)		1.01KG	0.99 KG	0.81 KG	0.80KG
Operating temperature		-10~50°C	-10~50°C	-10~50°C	-10~50°C
Operating humidity		10-95%	10-95%	10-95%	10-95%
Power consumption(approx.)		1.3-3.1W	1.2-2.7W	1.4-2.9W	1.4-2.7W
Connections					
LAN (PC port)		10/100Mb Ethernet	10/100Mb Ethernet	10/100Mb Ethernet	10/100Mb Ethernet
WAN (Internet port)		10/100Mb Ethernet	10/100Mb Ethernet	10/100Mb Ethernet	10/100Mb Ethernet
Adapter		Input: AC 100-240V Output: DC 5V/1.2A	Input: AC 100-240V Output: DC 5V/1.2A	Input: AC 100-240V Output: DC 5V/1.2A	Input: AC 100-240V Output: DC 5V/1.2A
PoE(802.3af) built-in		√	√	√	√
PoE(802.3af) class		Class 2	Class 2	Class 2	Class 2
Handset(RJ-9)		√	√	√	√
Headset(RJ-9)		√	√	√	√
Foot stand		√	√	√	√
Wall mounting		x	x	√	√
External device					
Yealink EXP38 expansion module		√	√	x	x
Yealink EXP39 LCD expansion module		√	√	x	x
Yealink EHS36 wireless headset adapter		√	√	x	x
Yealink YHS32 headset		√	√	√	√
User interface					
Display type		4.0"320x160 graphic LCD	3.1"132x64 graphic LCD	2.8"132x64 graphic LCD	2.7"2x15 characters LCD
LCD Backlight		√	√	√	√
Hard keys in all		48	45	32	31
Soft keys		4	4	4	x
Line keys		6	3	3	2
Memory keys		10	10	x	x
Programmable feature keys		14	14	11	9
Navigation keys		6	6	6	6
Volume key		√	√	√	√
Fixed feature keys		8 (Message/Headset/Conf/Hold/Mute/Tran/Redial/Handsfree)	8 (Message/Headset/Conf/Hold/Mute/Tran/Redial/Handsfree)	5 (Message/Headset/Tran/Redial/Handsfree)	9 (Menu/Hold/Conf/Contact/Message/Headset/Tran/Redial/Handsfree)
Power and ring indicator LED		√	√	√	√
SIP Accounts indicator LED		√	√	√	√
DSS keys with dual color LED		√	√	x	x
Message indicator LED		√	√	√	√
Headset indicator LED		√	√	x	x
Voice					
HD voice		HD Codec HD Speaker HD Handset	HD Codec HD Speaker HD Handset	HD Codec HD Speaker HD Handset	HD Codec HD Speaker HD Handset
Wideband codec		G.722	G.722	G.722	G.722
G.711 A-law/μ-law		√	√	√	√

G.726	√	√	√	√
G.723.1	√	√	√	√
G.729AB	√	√	√	√
VAD (Voice activity detection)	√	√	√	√
CNG (Comfort noise generator)	√	√	√	√
AEC (Acoustic echo canceling)	√	√	√	√
PLC (Packet loss concealment)	√	√	√	√
AJB (Adaptive jitter buffer)	√	√	√	√
AGC (Automatic gain control)	√	√	√	√
Side tone	√	√	√	√
Telephony features				
SIP Accounts	6	3	3	2
Hands-free speakerphone	Full Duplex	Full Duplex	Full Duplex	Full Duplex
Redial	√	√	√	√
Auto redial	√	√	√	√
Mute	√	√	√	√
3-way conferencing	√	√	√	√
Caller ID display	√	√	√	√
Call hold	√	√	√	√
Call waiting	√	√	√	√
Call transfer(blind/attended)	√	√	√	√
Call forward	√	√	√	√
Call History (all/misssed/ received/dialed/forwarded)	100 entries	100 entries	100 entries	100 entries
DND	√	√	√	√
SMS	√	√	√	x
Voice mail	√	√	√	√
Message waiting indicator(MWI)	√	√	√	√
Speed Dial	√	√	√	√
Ringtone selection	√	√	√	√
Volume control	√	√	√	√
Import of individual ringtone	√	√	√	√
Tone setting	√	√	√	√
Local Phonebook	1000 entries	1000 entries	1000 entries	1000 entries
Phonebook search/import/export	√	√	√	√
Intelligent search method	√	√	√	x
Black list	√	√	√	√
Keypad lock	√	√	√	√
LCD display logo	√	√	√	√
# or * key as Send function	√	√	√	√
Hotline	√	√	√	√
Localized language	English,German,French,Italian, Polish,Portuguese,Trukish,Spanis h	English,German,French,Italian, Polish,Portuguese,Trukish,Spanis h	English,German,French,Italian, Polish,Portuguese,Trukish,Spanis h	English,German,French,Italian, Polish,Portuguese,Trukish,Spanis h
Reset to factory	√	√	√	√
View Voice Mail	√	√	√	√
Headset (Call center mode)	√	√	√	√
Advanced features				
XML browser	√	√	√	x
Hot-desking	√	√	√	x
OpenVPN	√	√	√	√
LDAP phonebook	√	√	√	x
Soft key programmable	√	√	√	x
IP PBX and IP Centrex features				
BLF(Busy Lamp field)	√	√	√	√
BLA(Bridged Line Appearance)	√	√	√	√
Paging	√	√	√	√
Intercom	√	√	√	√
Call park	√	√	√	√
Call pickup	√	√	√	√
Call completion	√	√	√	√
Call recording	√	√	√	√

Anonymous call	√	√	√	√
Anonymous call rejection	√	√	√	√
Auto answer	√	√	√	√
Emergency call	√	√	√	√
Call return	√	√	√	√
Group listening	√	√	√	√
Distinctive Ringtone	√	√	√	√
Music on hold(via PBX)	√	√	√	√
Music on hold(via sever)	√	√	√	√
Dial Plan	√	√	√	√
Dial now	√	√	√	√
PUSH XML	√	√	√	x
Get balance	√	√	√	√
Web Interface				
Embedded web server	HTTP/HTTPS	HTTP/HTTPS	HTTP/HTTPS	HTTP/HTTPS
Edit phonebook via web	√	√	√	√
Send SMS via web	√	√	√	x
Dial via web	√	√	√	√
Web logout	√	√	√	√
Network and Time				
WAN Static IP/DHCP/PPPoE	√	√	√	√
PC port mode	Bridge/Router	Bridge/Router	Bridge/Router	Bridge/Router
DHCP server for PC port	√	√	√	√
SNTP/NTP	√	√	√	√
Setup date and time by manual	√	√	√	√
Daylight saving time	√	√	√	√
DNS Cache	√	√	√	√
VLAN	Auto configuration through DHCP/LLDP	Auto configuration through DHCP/LLDP	Auto configuration through DHCP/LLDP	Auto configuration through DHCP/LLDP
IPv6	ICMPv6, Static	ICMPv6, Static	ICMPv6, Static	ICMPv6, Static
Action URL& Action URI	√	√	√	√
Multicast IP Paging	√	√	√	√
Security				
HTTPS	√	√	√	√
TLS (Transport Layer Security)	√	√	√	√
SRTP (RFC3711)	√	√	√	√
802.1x	√	√	√	√
3-level privilege	Admin/VAR/User	Admin/VAR/User	Admin/VAR/User	Admin/VAR/User
Quality of Service(QoS)	802.1p/Q, ToS/DSCP	802.1p/Q, ToS/DSCP	802.1p/Q, ToS/DSCP	802.1p/Q, ToS/DSCP
AES for auto-provision	√	√	√	√
Management				
Configuration via LCD	√	√	√	√
Configuration via web	√	√	√	√
Configuration via autoprovision	√	√	√	√
Automatic firmware update	√	√	√	√
Manual firmware update	√	√	√	√
Auto provisioning via LCD	√	√	√	√
Auto provisioning via Web	TFTP/FTP/HTTP/HTTPS	TFTP/FTP/HTTP/HTTPS	TFTP/FTP/HTTP/HTTPS	TFTP/FTP/HTTP/HTTPS
Auto provisioning with PnP	√	√	√	√
Provisioning redirection (via phone)	√	√	√	√
Package tracing export	√	√	√	√
System log export	√	√	√	√
SNMP	√	√	√	√
TR-069	√	√	√	√
Redundancy Server	√	√	√	√
Broadsoft Advanced Features				
DND & Forward synchronization	√	√	√	√
Network Call Logs	Basic	Basic	Basic	x
Shared Call Appearance	√	√	√	√
Network Conference	√	√	√	√

BLF List	√	√	√	√
Call Forward	√	√	√	√
Call Pickup	√	√	√	√
Call Park	√	√	√	√
Call Center Features	√	√	√	√
Contacts	Custom/Enterprise/Personal/ Common/Search/Speed Dial	Custom/Enterprise/Personal/ Common/Search/Speed Dial	Custom/Enterprise/Personal/ Common/Search/Speed Dial	x
Alert-Info	√	√	√	√
BroadWorks Anywhere	√	√	√	√
Sequential Ring	√	√	√	√
Simultaneous Ring Personal	√	√	√	√
Anonymous Call	√	√	√	√
Anonymous Call Rejection	√	√	√	√
Remote Office	√	√	√	√
CosmoCom Advanced Features				
ACD	√	√	√	√
SIP				
SIP v1 (RFC2543)	√	√	√	√
SIP v2 (RFC3261)	√	√	√	√
UDP/TCP/TLS	√	√	√	√
Out-of-band DTMF(RFC 2833)	√	√	√	√
In-band DTMF	√	√	√	√
SIP INFO DTMF	√	√	√	√
STUN client (NAT traversal)	√	√	√	√
Rport (RFC3581)	√	√	√	√
Digest/basic authentication	Digest (MD5)	Digest (MD5)	Digest (MD5)	Digest (MD5)
Peer-to-peer SIP link mode	√	√	√	√
Loose routing and strict routing support	√	√	√	√
PRACK (RFC3262)	√	√	√	√
Error-information support	√	√	√	√
Reliability of provisional responses (RFC3262)	√	√	√	√
DNS SRV (RFC3263), redundant server support	√	√	√	√
Offer/answer (RFC3264)	√	√	√	√
Message Waiting Indication (RFC3842)	√	√	√	√
Subscription for MWI events (RFC3265)	√	√	√	√
Dialog-state monitoring (RFC 4235)	√	√	√	√
REFER (RFC3515)	√	√	√	√
Event list subscription support (RFC4662)	√	√	√	√
Other features				
Certification	CE/FCC/A-tick	CE/FCC/A-tick	CE/FCC/A-tick	CE/FCC/A-tick
Broadsoft Validated	√	√	√	√
Asterisk/Digium Certificated	√	√	√	√
Packing				
Giftbox size	285mm x 240mm x 110mm	285mm x 240mm x 110mm	220mm x 241mm x 105mm	220mm x 241mm x 105mm
PCS/CTN	5 PCS	5 PCS	10 PCS	10 PCS
Carton measure	580mm x 295mm x 250mm	580mm x 295mm x 250mm	560mmx460mmx250mm	560mmx460mmx250mm
N.W	6.9 KG	6.9 KG	11.8 KG	11.7KG
G.W	7.6 KG	7.6 KG	13 KG	12.9 KG
Note: the grid filled with color  means the new feature the grid filled with color  means the optimized feature				